

HAZARD SYMBOLS

HAZARDS

Medical

Toxic

Cuts

Burns

Eye **⊕н ⊕м ⊕** L LH LM LL Nose Mouth Hand €H €M€L **Poisonous Explosive** Corrosive Carcinogen Flammable Fatal Narcotic Allergies DO NOT USE **Toxic Gas** Death

SAFETY PRACTICES

Wet Mop	4
Ventilation	**
Dustmask	Q
Gloves	41
Wash hands	3
Avoid Ingestion	
Proper Storage	\Box
Goggles	60
Avoid Flame	

1. Provide	(CLEPIL			211
2. 013TQL	(ES)			2,12
a despe	strant en	•		2,12
4				2.12
E-PARTS				2.14 2.14
				2.14 2.16
				2.16 2.18
				2.18 2.18
		BOLLAN NO DESCRI		2.16
				220
				720
				270
				2 22 2 23
				7.26 2:50
				2日 2位
				2.12

In painting, one is exposed to many extremely toxic chemicals in paint pigments and many highly toxic vapours in solvents, esters, aromatic hydrocarbons and preservatives.

General safety practices would require a dust-free, clean environment, proper ventilation, and safe storage practices.

It is extremely important to avoid the inhalation of highly toxic dusts, pigments, and vapours, to avoid ingestion of any chemicals, and to protect the skin from any irritating substances.

MATERIAL	SYMBOL	HAZARD
DISTILLATES Used in paint thinners and general solvents such as:		
gasoline mineral spirits kerosene petroleum ether phenol turpentine varsol		Eye irritant Respiratory irritant may cause pulmonary edema and allergies Narcotics Skin irritant
DYES See FABRIC section		
EPOXY RESIN Used in: color resists casting laminating ashesive glue rubber cement	∠ H	Respiratory irritant and allergies Skin irritant and allergies

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
♦ ₩ 80	AVOID with elementary students Wear goggles AVOID inhalation Use with hood vent or outdoors Wear rubber gloves	Use water-based paints
	Tree value grant	
Ø ₩	AVOID use with elementary students Wear goggles Use respirator, hood vent, or use outdoors	
		·

MATERIAL	SYMBOL	HAZARD
PAINTS	J D M	GENERAL Pigment poisoning by inhalation of dust and sprays, by ingestion, and by contact with cuts and wounds
ACRYLIC PAINTS Contain: mercury preservatives ammonia formaldehyde	⊕ H ⊕ L し	Toxic by ingestion Allergic reactions Eye irritant Allergic reactions
FRESCO PAINTS Lime Lime water	# # # # � ∖♪� ()	Corrosive to eyes and lungs Corrosive by ingestion Corrosive by skin contact

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
₩ ₩ ₩	Use hood vent or proper respirator or a mixing box when mixing powder paints or using spray paints AYOID ingestion Keep all foods out of studio and avoid pointing brush with lips AYOID exposure of cuts and wounds. Use gloves to protect cuts Wash hands thoroughly after painting	Water-based paints are the least hazardous of the liquid paints Use coloured pencils, wax crayons or pastels for the very young students
(h. ⊗ ()	AVOID with division 1 elementary students AVOID ingestion Wash hands thoroughly after use	Use powder paints mixed with laundry starch
₩ \$ 0	AVOID with elementary students Wear goggles AVOID inhalation Use with hood vent or outdoors Wear gloves	Use acrylic paints

MATERIAL	SYMBOL	HAZARD
OIL PAINTS Pigment	A	Fume may cause respiratory irritation Pigment poisoning
Contain stabilizers and driers such as: cobalt	س ه	Respiratory irritant May effect skin and mucous membranes and possibly cause allergies
lead mangane se	∠ H ⊕ H	Highly toxic if used as pure drier in printmaking
PIGMENTS Finely ground insoluble colouring matters. Many are highly toxic substances, such as: Aluminum Antimony * Arsenic * Barium * Cadmium Chromates * Cobalt * Lead Manganese Mercury Oxides Sulfides Zinc * most dangerous	J. D. M.	Most severe hazards from: Inhalation Ingestion Cuts and wounds Health is affected from minor ailments: Spasms Yomiting Headaches Weakness To very severe and fatal condition: Allergies—skin,respiratory Asthma Blood disease—anemia Bone damage Cancer—lung, skin Fibrosis Gastrointestinal problems Kidney damage Liver damage Nervous system diseases Poisoning—acute to fatal Loss of smell

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
⊗	AVOID inhalation and ingestion See general PAINT safety precautions	Use water-base paints
	AVOID inhalation and ingestion See general PAINT safety precautions	Use water-base paints
	AYOID inhalation of powders and spray paint	Use premixed liquid paint
*	AYOID grinding of pigment AYOID spraying whenever possible Use proper venting Use proper respirator	
⊗	Mix powders near slot vent, inside dust box, or in bucket covered with moist cloth To avoid dust, teach children safe mixing and working procedures Practice careful personal hygiene to avoid ingestion	

MATERIAL	SYMBOL	HAZARD
PAINTS POWDER PAINTS	∠ + ⊕ +	Pigment poisoning
SPRAY PAINTS AEROSOL SPRAYS Used with spray guns spray cans air brushes contain: organic solvents butane carbon dioxide fine particles TEMPRA BLOCKS	桑 終	OENERAL Respiratory dangers caused by fine spray which contains fine particles of resins, paint, or laquer and can remain suspended in the air for hours Olfactory fatigue sets in and you no longer smell the spray Chronic poisoning from toxic pigments High pressure guns can cause pigment injection under the skin which may require amputation Aerosol cans are highly explosive Dust from blocks and paintings may be toxic
PASTELS/ CHALKS See DRAWING section May contain: asbestos	Ø. ∠m	AYOID ingestion AYOID creation and breathing of dust

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
ಶ	AVOID inhalation Use safe mixing practices	
*	GENERAL AVOID use with elementary students AVOID paint with highly toxic pigments such as lead or zinc chromate, known carcinogens AVOID using mouth atomizers Use fume hood, approved mist respirator, or paint spray respirator Wear gloves Do not use near open flame	Stipple the paint with brush or sponge Use tooth brush or stencil brush for splatter effect
Ð	AYOID inhalation of pigment dust AYOID ingestion Wash hands after use Protect open wounds	
1	Wet mop cleanup	Use wax crayons, conte sticks, oil pastels

MATERIAL	SYMBOL	HAZARD
PRESERVATIVES Used in paint to give a longer shelf life	☆ ८ ♦	Some are highly toxic by inhalation and ingestion May cause acute but not chronic illness
SEALERS Lacquers Varnishes contain Esters isomyl acetate butyl acetate ethyl acetate	ال ا	Eye irritant Respiratory irritant Skin irritant May form highly toxic phosgene when exposed to flames and ultraviolet light
SOLVENTS Have many uses: to dissolve and mix oils, resins, and varnishes to remove lacquers, paints, and varnishes to clean tools, surfaces, and hands	₩ 3000	GENERAL One of the most underrated art hazards Almost all are poisonous and some are lethal in small doses, inhaled or ingested Narcosis or central nervous system depression. Symptoms: dizziness, headaches, loss of coordination, mental confusion, coma and death

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
	Wear vapor respirator Use in liquid form rather than powder form avoid ingestion Wear gloves	Use safer products such as: oil of cloves, sodium benzoate, propyl paraben Use redimix paint
Ø ##	AVOID use with elementary students AVOID inhalation Use under hood vent or outdoors Wear proper gloves	Use acrylic or polymer medium to seal surfaces where applicable
	GENERAL AYOID with elementary students AYOID inhalation , ingestion, and skin contact Use proper ventilation Cover all containers to prevent evaporation AYOID lethal kind: benzene -benzol carbon tetrachloride	Use water-base paints, inks, felts, and glues rather than solvent-based materials Use butter, margarine, or vaseline to clean skin Use the least toxic solvents such as: ACETONE ETHANOL -denatured alcohol or grain alcohol ISOPROPYL ALCOHOL MINERAL SPIRITS- especially odorless paint thinners with aromatic hydrocarbons removed

MATERIAL	SYMBOL	HAZARD
SOLVENTS ALCOHOL Methanol wood alcohol methyl alcohol rubbing alcohol	∠ Η ⊕ Η	Affects the nervous system causing dizziness, nausea, intoxication, blurred vision Possible liver and kidney damage Blindness and death
Amyl alcohol fusel oil	∠ Η	Effects the nervous system May cause dizziness, nausea, vomiting, or double vision
Butyl alcohol	6 M	Eye, nose, and throat irritation
isopropyl alcohol	ر M	Moderate to low toxicity
Ethyl alcohol grain alcohol	~ (M	Liver damage
Benzyl alcohol	۷۱	Low toxicity
		·

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
% ‡ ⊗ 0	AVOID inhelation AVOID ingestion AVOID skin contact Use proper ventilation	Use ETHANOL – a denatured alcohol containing smaller amounts of methanol
}		

MATERIAL	SYMBOL	HAZARD
AROMATIC HYDROCARBONS Are among the most dangerous solvents Used in: paints varnish removers lacquers inks plastic solvents		GENERAL Strong narcotic properties Pulmonary edema Skin irritant Highly flammable Chronic poisoning from cumulative small amounts
Benzene	₩ H	Destroys bone marrow causing aplastic anemia Carcinogen Highly flammable_flash point 12 degrees F. minus 11 degrees C.
Toluene toluol aromatic naphtha		Chronic liver and kidney damage Heart sensitization and death Adverse effect on reproductive organs May cause skin defatting Flammable- flash point 45 degrees F. 7 degrees C.
Xylene/ Xylol Used in: lacquer thinner Washup		See toluene

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
* 0	GENERAL With elementary students use outdoors or avoid use	
	Use with fume hood	
	Use an organic respirator	
	Keep all containers closed	
41	Wear gloves	
	AVOID skin contact	
0	AYOID use	Use water-based paints
		Use the less dangerous solvents ACETONE or ETHANOL-grain alcohol
0	Avoid use	Use water base paints
	Keep at temperatures below 45 degrees F. 7 degrees C.	Use the less dangerous solvents ACETONE or ETHANOL – grain alcohol
0	AYOID use	ACETONE- only slightly toxic but highly flammable

MATERIAL	SYMBOL	HAZARD
AROMATIC HYDROCARBONS Styrene Uses: resin solvent paint remover varnish remover silkscreen washup lacquer thinner aerosol sprays	★ 3 + € +	Possibly more toxic than toluene and xylene Respiratory irritation Narcosis Damage to liver, kidney, and nervous system
CHLORINATED HYDROCARBONS	욧	GENERAL Liver and kidney damage Dangerous in combination with alcohol Dissolves the fatty layer of skin-dermatitis Forms the highly toxic gas phosgene in presence of heat and ultraviolet light
Carbon tetrachloride	∠ H	Suspected carcinogen Severe liver and kidney damage Fatal in large exposure, especially in combination with alcohol
Chloroform phosgene gas		Carcinogen— liver cancer Forms highly toxic phosgene gas
Methyl styrene	() H (⊕ H	Possible liver, nervous system and blood damage Narcosis

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
0	AVOID use	ACETONE (highly flammable) ETHANOL
1	GENERAL AVOID inhalation AVOID ingestion AVOID skin contact Keep all containers closed to avoid evaporation AVOID USE	GENERAL Use the least toxic solvents: ACETONE ETHANOL – grain alcohol ISOPROPYL ALCOHOL MINERAL SPIRITS – especially the odorless paint thinners that have the aromatic hydrocarbons removed
0	AVOID USE	
0	AYOID USe	·

2.27

MATERIAL	SYMBOL	HAZARD
CHLORINATED HYDROCARBONS	桑	
Methylene chloride	₩	Severe respiratory irritant Narcosis Forms carbon monoxide in the body and has caused
	必	fatal heart attacks Highly volatile
Tetrachloroethylene Tetrachloroethane phosgene gas		Severe damage to blood, liver and nervous system, as well as gastrointestinal system Produces highly toxic phosgene gas in the presence of flames or ultraviolet light
Perchloroethylene phosgene gas	ر ن⇔ ا	Narcosis, liver damage, carcinogen Produces highly toxic phosgene gas in the presence of flames or ultraviolet light
Ethylene dichloride phosgene gas	C⊕H €M	Liver cancer Produces highly toxic phosgene gas in the presence of flames or ultraviolet light
	A	Fatal when inhaled in high concentration

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
Ø ₽	AVOID USE— especially smokers, people with heart problems, and the elderly	Use the least toxic solvents: ACETONE ETHANOL— grain alcohol ISOPROPYL ALCOHOL MINERAL SPIRITS— especially the odorless paint thinners that have the aromatic hydrocarbons removed
0	AVOID USE in presence of flame or ultraviolet light	
0	AVOID USE in presence or flame or ultraviolet light	
0	AVOID USE	
		·

2.29

MATERIAL	SYMBOL	HAZARD
PETROLEUM DISTILLATES Uses: paint thinners rubber cement silkscreen cleanup solvents	C → H S → M	GENERAL Ingestion may cause pulmonary edema, chemical pneumonia and possible death Skin irritant Highly flammable
N-hexane	と出	Extremely volatile Nerve damage and possible paralysis of arms and legs Permanent damage to central nervous system with high exposure
Gasoline	**	Flammable- flash point minus 50 degrees F. minus 46 degrees C.
Benzine	*	Flammable- flash point 20 to 55 degrees F. minus 7 to 13 degrees C.
Mineral spirits odorless paint thinner turpentine substitutes white spirits	※	Flammable— flash point 86 to 105 degrees F. 30 to 40 degrees C.
Kerosene	***	Flammable- flash point 100 to 165 degrees F. 38 to 74 degrees C.

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
A	GENERAL Do not store rags used for petroleum distillates	Use water-based paints, glues, and pens
0	AVOID inhalation	
	AVOID ingestion	
	AVOID skin contact	
*	Use proper ventilation	
	Seal containers to avoid evaporation	

2.31

MATERIAL	SYMBOL	HAZARD
SOLVENTS		
ESTERS	•	Eye irritant
Uses: Lacquers	Z M	Respiratory irritant
Resins		Anesthetic effects
Plastic solvents	⇔ H	
which may contain ethyl acetate	€L	
methyl acetate amyl acetate		-
GLYCOLS AND DERIVATIVES		
Uses:		
Paint		
Aerosol sprays		
Lacquer thinners		
which may contain:		
methyl cellosolve butyl cellosolve	С н Ө н	Anemia and kidney damage
cellosolve		Birth defects, miscarriages and sterility, even at low exposure levels
	€ `H	
KETONES	©	Eye irritant
Uses:	6 H	Respiratory irritant- large amounts can cause
Lacquers Oil		narcosis
Plastics	⇔н	Ingestion causes vomiting, nausea, and abdominal
Waxes		pain, pulmonary edema and kidney damage
Inks		·
isophorone methyl butyl ketone	€ H	

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
© ₩ Ø	Wear goggles Use proper ventilation AYOID inhalation, digestion and eye contact	Use water-based materials
* 0	Use proper ventilation AVOID ingestion , inhalation, and skin contact	Use water-based materials
Ø ☆	AVOID inhalation, ingestion, and skin contact Use proper ventilation	ACETONE- flash point 15 degrees F. minus 10 degrees C. - extremely flammable
	Close containers well to avoid evaporation Discard rags in proper container Highly flammable	·

MATERIAL	SYMBOL	HAZARD
SOLVENTS ACETONE		A safer solvent except for high flammability
Methyl ethyl ketone M.E.K.	₩ ⊕ M	No lasting physical effects More toxic than acetone May cause peripheral neuropathy
Cyclohexanone	\\ \(\Phi \) \\\ \(\Phi \) \\ \(\Phi \) \\\ \(\Phi \) \\\\ \(\Phi \) \\\ \(\Phi \) \\\\ \(\Phi \) \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Damage to nervous system
Turpentine	SA SA SA SA SA SA SA SA SA SA SA SA SA S	Respiratory irritant Headaches Skin irritant and sensitizer Gastritis, anxiety, mental confusion Highly poisonous—1 tablespoon ingested may be fatal to a child

2.34

SYMBOL	SAFETY PRACTICE * CLEAN-UP	ALTERNATIVES
0	AVOID USE with elementary children	ACETONE
		·

2.35

PIGMENTS

<u>PIGMENTS</u> are finely ground substances that give colour to the various colouring media such as paints-oil, acrylic, tempera, epoxy, fresco, pastels-crayons, pencils, chalks, inks and dyes.

HEALTH HAZARDS arise maily from inhalation of fine pigment dust and paint sprays and from ingestion of pigments when pointing a brush with the lips or neglecting careful hygiene and housekeeping precautions.

SAFETY PRACTICES:

Avoid pigment grindings and mixing as well as paint spraying if, at allpossible. Use hood vents, mixing boxes, appropriate respirators, goggles and gloves to avoid the inhalation and ingestion of these highly toxic substances.

Eat, drink and smoke with clean hands only, and avoid contamination of open wounds and abrasions.

PLEASE NOTE:

In the following charts, colours are named both by popular name and by colour code. The latter identifies colours according to chemical composition.

Pigments are among the most highly toxic substances for our bodies. The list below bears this out. Note, the stars mark the most dangerous among them. These must be respected for their severe and, at times, fatal effects on the human body, including conditions such as: anemia, bone damage, lung and skin cancer, fibrosis, gastrointestinal problems, kidney and liver damage, nervous system diseases, loss of smell and acute to fatal poisoning.

Aluminum

Antimony

- * Arsenic
- * Barium
- * Cadmium Chromates
- * Cobalt -
- * Lead

Manganese

Mercury

Oxides

Sulfides

Zinc

COLORS WITH NO SIGNIFICANT HAZARDS

COLOUR	POPULAR NAME	COLOUR CODE
YELLOW	YELLOW OCHRE MARS YELLOW	Yellow 42/43 Yellow 42
RED	VENETIAN RED MARS RED TERRA ROSA ROSE MADDER ALIZARIN CRIMSON	Red 101 Red 101 Red 101 Red 83 Red 83
BLUE	ULTRAMARINE BLUE	Blue 29
GREEN	ULTRAMARINE GREEN	
VIOLET	ULTRAMARINE VIOLET	Violet 15
BROWN	RAW SIENNA BURNT SIENNA	Brown 6 Brown 6
WHITE	TITANIUM WHITE BARIUM WHITE	White 6 White 21/22
BLACK	MARS BLACK IVORY BLACK	Black 11 Black 9

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT	HAZARDS
ANTIMONY	∠ + ⊕ +	Antimony White/White 11	Acute indigestion or inhalation: metallic taste, vomiting, diarrhea, severe mouth and nose irritation, pulmonary congestion Chronic exposure: loss of
			appetite and weight, insomnia, nausea, headache, even liver and kidney damage
	€ H		Skin contact: severe lesions and ulcers
ARSENIC	4	Scheele's Green/Green 22	Chronic inhalation: lung cancer
Copper Arsenite	⇔ н		Chronic ingestion: demage to kidney, liver, blood and peripheral nervous system
			Acute indigestion: fatal arsenic poisoning
	€ H		Carcinogen -skin cancer
BARIUM	∠ H ↔ H		Acute inhalation and ingestion: BARIUM POISONING - severe muscle pain, intestinal spasms, heart irregularities
			Respiratory allergies Lung cancer

TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
4	Barium Yellow/-	See above
	Barium White/White 21 or 22	No specific hazard
L H	Manganese Blue/Blue 33	Acute inhalation: BARIUM POISONING
⇔ н		Chronic ingestion: MANGANESE POISONING, a serious nervous system disorder similar to Parkinson's disease
		Early symptoms: Loss of appetite, weakness, spasms, headaches and irritability
6 H	Barium Yellow	Respiratory allergies Carcinogen: lung cancer
⇔ #		BARIUM POISONING
₩	Lithol Red / Red 49	BARIUM POISONING
10 10 10 HH HH	Cadmium Orange/ Orange 20 Cadmium Red/Red 108 Cadmium Yellow/ Yellow 35 & 37	In all three colours, the CADMIUM content causes, with chronic intake: kidney damage, loss of smell, gastro-intestinal problems, bone, teeth and liver damage as well as prostate and lung cancer
	RATING	AH Barium Yellow/- Barium White/White 21 or 22 AH Manganese Blue/Blue 33 → H Barium Yellow → H Lithol Red / Red 49 AH Cadmium Orange/Orange 20 AH Cadmium Red/Red 108 AH Cadmium Yellow/ AH Cadmium Yellow/ AH Cadmium Yellow/

TABLE OF HAZARDOUS PAINT PRODUCTS

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
Cadmium Sulfide and Mercuric Sulfide	⊘ н	Cadmium Vermillion Red/ Red 113	In addition to the above: MERCURY POISONING which severely damages the nervous system and kidneys Skin allergies
CARBON	€ M	Carbon Black/Black 6 Lamp Black/Black 6	Chronic inhalation may result in respiratory irritation Repeated skin contact may cause skin cancer
CHROMATES	∠ H ⊕ H € M		Carcinogen Teratogen- causes fetal monstrosities Suspected mutagen- causes genetic changes Lung cancer, respiratory
			allergies and perforation of nasal septum CHROMIUM POISONING: kidney damage, muscle cramps, vertigo, gastroenteritis
Barium Chromate		Barium Yellow/	See above
Zinc Chromate		Zinc Yellow/Yellow 36	See above
Strontium Chromate		Strontium Yellow/ Yellow 22	Lung cancer, CHROMIUM poisoning, Skin allergies and ulcers

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
Lead Chromate	7\$€ \$	Chrome Green/Green 15 Milori Green/Green 15	Also LEAD POISONING
Lead Chromate		Chrome Yellow/Yellow 34 Chrome Orange	CHROMIUM POISONING
Barium Chromate	J\$# ₩	Lemon Yellow/	Also: BARIUM POISONING, heart irregularities, intestinal spasms, sever muscle pain
COBALT			Repeated skin contact: allergies, especially at neck, ankles and elbows
			Chronic inhalation: asthma and possible fibrosis Ingestion: Acute illness with vomiting, diarrhea and hotness
Cobalt Cobalt Oxide Cobalt Oxide Cobalt Phosphate Cobalt Arsenate	ム M M H H M M M H H M M	Cerulean Blue/Blue 35 Cobalt Blue/Blue 28 Cobalt Green/Green 19 Cobalt Violet/Violet 14 Cobalt Violet/ Violet 77350	See above See above See above See above Skin allergies As above and in addition:skin ulceration, acute fatal poisoning, chronic ingestion or inhalation May cause digestive disturbances and general damage to liver, kidney, blood and peripheral nervous system

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
Potassium Cobalt Initrite	3 ⊅ €	Cobalt Yellow/Yellow 40	Ingestion: Acute poisoning. Chronic effect: Drop in blood pressure, headaches, rapid pulse, visual disturbances
COPPER Copper Acetoarsenite	\} ♦ ₩	Emerald Green/Green 21	Human carcinogen: Skin and lung cancer Chronic exposure may cause damage to liver, kidney, blood, peripheral nervous system and digestive system Acute ingestion: Fatal ARSENIC POISONING
CYANIDE Phthalocyanide Phthalocyanide Ferric Ferrocyanide	7\$€ 3\$€	Thalo Blue/Blue 15 Thalo Green/Green 7 Prussian Blue/Blue 27 Paris Blue/Blue 27 Berlin Blue/Blue 27	Usually contaminated by PCB's which are a suspected carcinogen and teratogen- causes birth defects Same as Thalo Blue Harmless by itself but can form extremely toxic hydrogen cyanide gas when heated or when exposed to ultraviolet radiation

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
SULFIDES	.⇔ H		
Barium Sulfate Zinc Sulfide Zinc Oxide		Lithopone/White 5	Zinc sulfide might react with stomach acids to produce the highly toxic gas hydrogen sulfide
LEAD	U ⊕ H		LEAD POISONING: Affects the gastrointestinal system (lead colic), red blood cells (anemia) and the neuromuscular system affecting wrists, fingers, ankles and toes Other common effects include weakness, irritability, pain in joints and muscles, liver and kidney damage and possible birth defects
Lead Chromate	\(\frac{\ph}{\ph}\)	Chrome Green/Green 15	Lung cancer Perforation of nasal septum Allergies CHROMIUM POISONING LEAD AND CHROMIUM POISONING
Lead Carbonate Zinc Oxide	∠ H	Mixed White/White 1 Flake White/White 1 White Lead/White 1	Both acute and chronic intake can cause LEAD POISONING

TABLE OF HAZARDOUS PAINT PRODUCTS

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
Lead Chromate Lead Molybdate Lead Sulfate	13 ⊕ €	Molybdate Orange/ Red 104	Carcinogen Teratogen Suspected mutagen LEAD & CHROMIUM POISONING
Lead Antimoniate	J ⊕ M	Naples Yellow/Yellow/41	Inhalation and ingestion: ANTIMONY POISONING- colic, vomiting, diarrhea, severe irritation of the mouth and nose, shallow breathing and pulmonary congestion Chronic exposure: liver and kidney damage and LEAD POISONING
MANGANESE	⇔ Η		MANGANESE POISONING is a serious nervous system disorder, very similar to Parkinson's disease. Early symptoms include: loss of appetite, apathy, spasms, headaches and irritability
Barium Manganate	Дн Ө н	Manganese Blue/Blue 33	MANGANESE POISONING Also BARIUM POISONING
		Manganese Violet/ Violet 16	Chronic exposure: MANGANESE POISONING
Manganese Silicates	Д н ⇔ н	Raw Umber/Brown 7	Chronic exposure: MANGANESE POISONING

TABLE OF HAZARDOUS PAINT PRODUCTS

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
MERCURY	7.Φ€ # # #		Inhalation or ingestion can result in MERCURY Poisoning which damages the kidneys and the nervous system
Mercuric Sulfide		Vermillion/Red 106	Mercury POISONING Skin allergies
OXIDES Iron Oxides Iron Oxides Iron Oxides		Mars Black/Black 11 Burnt Sienna/Brown 6 Mars Red/Red 101 English Red/Red 101 Light Red/Red 101	No specific hazards. No significant hazards. No significant hazards
Manganese Dioxide	⇔ Η	Burnt Umber/Brown 7 Mars Brown/Brown 7	Chronic inhalation - serious nervous disorder resembling Parkinson's disease
Cobalt and Tin Oxides	©r ⊕r	Cerulean Blue/Blue 35	Chronic inhalation may lead to asthma and fibrosis Ingestion may cause acute illness with vomiting, diarrhea and sensation of hotness
Chromic Oxides	∠M ⊕L €M	Chromium Oxide Green/ Green 17	Skin and respiratory irritation and allergies Possible carcinogen

PIGMENT	TOXICITY RATING	COLOUR/ PIGMENT CODE	HAZARDS
Iron Oxide		Mars Yellow/Yellow 42	No significant hazards
Titanium Dioxide		Titanium White/White 6	No significant hazards
ZINC Zinc Oxide	L	Zinc White/White 4 Chinese White/White/4	Inhalation and ingestion: slight irritation
Zinc Chromate	L	Zinc Yellow/Yellow 36	See Chromates
Zinc Sulfide	⊕ H	Lithopone/White 5	Zinc Sulfide might react with digestive acids to form a highly toxic gas - hydrogen sulfide

SOLVENTS

The most effective precaution with solvents is to eliminate all that are not absolutely necessary. High quality water based paints and inks have reduced the necessity for many solvents.

If solvents are necessary, the following precautions should be taken:

- 1. Rooms must be properly vented.
- 2. Do not use paint stripper or varnish remover as they are one of the most hazardous of solvents.
- 3. Use lacquer thinners with extreme care.

In general terms, a flammable liquid is a fire hazard under normal conditions and use. It is combustible if it becomes a fire hazard when heated.

The fire hazard of a liquid is expressed in terms of its flash point. A flash point is the lowest temperature at which the liquid expels enough vapors to form an ignitable mixture with the air at the surface of the liquid.

A liquid is flammable if the flash point is below 100°F or 37°C. It is combustible if the flash point is at or above 100°F or 37°C. If a liquid has a flash point of below 20°F, it is considered to be highly flammable.

Class I Flammable Liquids

Acetone, benzene, ethyl alcohol, toluol (contained in some lacquer thinners), turpentine, and gasoline.

These liquids should not be stored or used in the art room as they are highly volatile (evaporate and vaporize rapidly).

Class II Combustible Liquids

Kerosene, mineral spirits, lithotine. These are not as hazardous as Class I materials, but should be stored in special containers and used with care.

SOLVENT - STORAGE AND HANDLING

Storage Containers for flammable and combustible liquids should be made of heavy metal with a self-closing lid. Never use breakable containers.

Storage Cabinets for flammable and combustible liquids should meet the National Fire Protection Association fire code (NFPA). They should be double-walled, built of 18 gauge metal and have tightly closing lockable doors. Have storage cabinets clearly labeled "Flammable - Keep Fire Away" and approved by the local fire marshal. Never leave open containers in storage cabinet.

Approved Waste Containers should be used for the disposal of rags and paper towels that have been used with flammable or combustible liquids. These containers should be constructed of sheet metal and have covers that close automatically. They should be emptied everyday and handled separately from regular waste according to school district or local policies.

BASIC RULES

- 1. Label containers clearly as to their contents and hazards.
- 2. Store in non-breakable containers (metal or plastic).
- 3. Store large containers on lower shelves to prevent danger of falling and breaking.
- 4. Store chemicals that may react together in separate areas.
- 5. Keep all containers closed even when working to prevent vapours and dusts from escaping into air.
- 6. Do not eat, drink, or smoke in studio.
- 7. Wear special clothes in studio. Keep separate and wash frequently.
- 8. Follow first aid procedures for accidental contact. Wash with lots of water. For eye contact, rinse for 15 minutes. Call doctor.
- 9. Wash hands frequently with soap and water after work, before eating and during work breaks. Never use solvents to clean hands. If necessary, use waterless hand cleaner, then soap and water.
- 10. Wear gloves or barrier cream to protect hands from solvents.
- 11. Wipe spills up immediately with paper towel and place in approved disposal unit.
- 12. Use a hand pump to dispense liquid that is stored in large containers (five-gallon drum).
- 13. Wear safety goggles when pouring liquids that can splash and cause eye damage.